

Download


DXF 2D
- sevilla2.dxf

Montaggi
- sevilla123.pdf



Sevilla 2 - 220/240V

Corps : aluminium moulé sous pression. Diffuseur : verre trempé transparent épaisseur 4 mm résistant au choc thermique et au choc mécanique. Équipement : étrier galvanisé et peint. Câble d'alimentation L = 0,6m. LED: facteur de puissance : 0,9. Maintien du flux lumineux à 80%: 50.000h (L80B20). Groupe de risque photobiologique: groupe 0 (exempt de risque).



Code	Gear	Kg	Lumen Output-K-CRI	WTot	Colour
22413431-00	CLD	0,61	LED-5200lm-3000K-CRI 80	50 W	GRAPHITE
22413432-00	CLD	0,61	LED-5500lm-4000K-CRI 80	50 W	GRAPHITE
22413433-00	CLD	0,61	LED-5500lm-6500K-CRI 80	50 W	GRAPHITE
22413431-19	CLD	0,61	LED-5200lm-3000K-CRI 80	50 W	GRAPHITE
22413432-19	CLD	0,60	LED-5500lm-4000K-CRI 80	50 W	GRAPHITE
22413433-19	CLD	0,65	LED-5500lm-6500K-CRI 80	50 W	GRAPHITE

The reported luminous flux is the flux emitted by the light source with a tolerance of $\pm 10\%$ compared to the indicated value. The W tot column indicates the total wattage absorbed by the system without exceeding 10% of the indicated